



ARM Supplies Ltd.

Technical Data Sheet

SANICA - Towel Warmers / Rail Ladder

							THERMAL OUTPUT Δt=50					
COLLECTORS & TUBES mm	WIDTH mm	WIDTH Inch	LENGHT mm	LENGTH Inch	NUMBER OF TUBES	WATER CAPACITY lt	Watt		Kcal/h		Btu/h	
							PAINTED	CHROME	PAINTED	CHROME	PAINTED	CHROME
COLLECTORS 30x40 mm D TUBES Ø 22 mm	300	11 6/8	700	27 4/8	13	2.2	210	150	181	129	716	512
	300	11 6/8	800	31 4/8	14	2.5	234	167	201	144	799	571
	300	11 6/8	1000	39 3/8	16	3.0	283	202	243	174	965	689
	300	11 6/8	1100	43 2/8	18	3.3	314	224	270	193	1070	764
	300	11 6/8	1200	47 2/8	20	3.6	345	246	296	212	1176	840
	300	11 6/8	1400	55 1/8	22	4.1	393	281	338	241	1341	958
	300	11 6/8	1500	59	24	4.5	424	303	365	260	1447	1033
	300	11 6/8	1600	63	26	4.8	455	325	391	279	1552	1109
	300	11 6/8	1800	70 7/8	30	5.4	517	369	444	317	1764	1260
	400	15 6/8	700	27 4/8	13	2.6	250	178	215	153	852	608
	400	15 6/8	800	31 4/8	14	2.9	277	198	238	170	945	675
	400	15 6/8	1000	39 3/8	16	3.5	332	237	285	204	1131	808
	400	15 6/8	1100	43 2/8	18	3.9	369	263	317	226	1258	898
	400	15 6/8	1200	47 2/8	20	4.3	406	290	349	249	1384	989
	400	15 6/8	1400	55 1/8	22	4.8	460	329	396	283	1570	1122
	400	15 6/8	1500	59	24	5.2	497	355	428	305	1697	1212
	400	15 6/8	1600	63	26	5.6	534	382	459	328	1823	1302
	400	15 6/8	1800	70 7/8	30	6.4	608	435	523	374	2076	1483
	500	19 5/8	700	27 4/8	13	3.0	289	207	249	178	987	705
	500	19 5/8	800	31 4/8	14	3.4	320	228	275	196	1091	779
	500	19 5/8	1000	39 3/8	16	4.0	380	272	327	234	1298	927
	500	19 5/8	1100	43 2/8	18	4.4	423	302	364	260	1445	1032
	500	19 5/8	1200	47 2/8	20	4.9	467	333	401	287	1592	1137
	500	19 5/8	1400	55 1/8	22	5.5	527	377	453	324	1799	1285
	500	19 5/8	1500	59	24	6.0	570	407	491	350	1947	1390
	500	19 5/8	1600	63	26	6.4	614	438	528	377	2094	1496
	500	19 5/8	1800	70 7/8	30	7.4	700	500	602	430	2388	1706
	600	23 5/8	700	27 4/8	13	3.5	329	235	283	202	1122	802
	600	23 5/8	800	31 4/8	14	3.8	362	259	312	223	1236	883
	600	23 5/8	1000	39 3/8	16	4.5	429	307	369	264	1464	1046
600	23 5/8	1100	43 2/8	18	5.0	478	342	411	294	1632	1166	
600	23 5/8	1200	47 2/8	20	5.5	528	377	454	324	1800	1286	
600	23 5/8	1400	55 1/8	22	6.2	594	425	511	365	2028	1449	
600	23 5/8	1500	59	24	6.8	644	460	553	395	2196	1569	
600	23 5/8	1600	63	26	7.3	693	495	596	426	2364	1689	
600	23 5/8	1800	70 7/8	30	8.3	791	565	681	486	2701	1929	

* Prepared theoretically on the basis of B09 671.2310 test done by HLK.

**The given values above were calculated theoretically, the actual values can be found by tests of accredited laboratory.